


Hilway Direct
12 McCullough Drive, Suite 10
New Castle, DE 19720
1-877-356-6748
Fax: 302-325-3801

Product Information



Hilway Direct Sealers

1. Product Description

Hard-wearing and highly resistant polymer sealer for the protection of **Capri cork Sequel**, **AND/OR**, and **Re-Tire** products (after installation or following stripping).

2. Areas of Application

All **Capri cork Sequel**, **AND/OR**, and **Re-Tire** products.

3. Method of Application

Before applying sealer, make sure that the floor surface is properly prepared. At a minimum the floor must be cleaned with a neutral pH cleaner. For heavily soiled or previously sealed flooring use only Schutz Stripper and Cleaner (available from Capri) to remove all existing coatings and residue. If the floor has been stripped, all residual stripper should be removed and the pH of the floor should be returned to neutral (6.5-7.5). Shake Hilway Direct Sealer well before use. Then apply an even, thin, undiluted coat to the surface of the cleaned floor using a new, clean string mop. It is important to pass the mop head in a figure 8 pattern to ensure that all areas are thoroughly covered. When the protective film has dried enough to walk on (approximately 1 hour), repeat the procedure in the crossways direction. Allow the film to dry for at least 12 hours before the floor is walked on, better still would be overnight.

Consumption: 1.3gal = 1076 ft² per coat.

Notes: Ensure that there is sufficient ventilation but avoid exposure to drafts and strong sunlight during application and drying processes and protect the surface from dust. Turn off under-floor central heating in good time prior to use.

4. Technical Data

Hilway Direct Sealers should be stored in a cool, dry place in its closed original container. Keep locked up and out of the reach of children. Protect from freezing.

VOC content: 0

The above advice on procedure for use is based on the best of our knowledge and the latest information available on cleaning technology. For this reason, when using our quality products, no damage will be incurred to the materials to be cleaned if strict attention is paid to the instructions printed on the container and the procedure suggested by us is followed. The use to which our products are put is, however, beyond our control. It is the responsibility of the user and does not release the user from making his own checks of the products supplied by us as to their suitability for the intended procedure and purposes. The information supplied by us is therefore non-binding and cannot be used as a basis for establishing the company's liability for any damage incurred. This also includes the infringement of any rights for the protection of third parties.